

LI-ION RECHARGEABLE

DICATA™ INTRINSICALLY SAFE DUAL-LIGHT USB HEADLAMP

XPR-5562GX

# NIGHTSTICK®

Life Depends on Light™



**MAGMATE™** Magnetic Coupler  
USB Rechargeable.



**Enlarged front-mounted dual switches**, easily toggle through the beam options with gloves on.



**Low Profile for Visor Clearance**, on most helmets & hard hats.



**Dual-Light Technology**, focused spotlight and area floodlight at the same time.

**CLASS I  
DIV 1**

**DUAL  
LIGHT®  
TECHNOLOGY**

**IP-67  
DUST/WATER  
PROOF**

**300 LUMENS**



1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

## LI-ION BATTERY

### ITEM NUMBER/UPC

- XPR-5562GX, UPC 0 17398 80774 6

### MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

### CERTIFICATIONS

- cULus, ATEX, IECEX, CE, NFPA

### CASE MATERIAL

- Engineered polymer

### SPOTLIGHT LUMENS/RUNTIME

- HIGH: 275L, 6 hrs. runtime

- LOW: 100L, 15 hrs. runtime

### FLOODLIGHT LUMENS/RUNTIME

- HIGH: 250L, 6 hrs. runtime

- LOW: 100L, 15 hrs. runtime

### DUAL-LIGHT LUMENS/RUNTIME

- 300L, 5 hrs. runtime

### CANDELA

- HIGH: 3,660

### BEAM DISTANCE

- 120 m

### WATER RATING

- ANSI IP-67 dustproof / waterproof

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 1.25 in (31 mm)

- WIDTH: 3.75 in (95 mm)

- DEPTH: 1 in (25 mm)

- WEIGHT: 5.8 oz (164 g)

### POWER SOURCE

- Integrated Li-ion

### WARRANTY

- Limited lifetime

### WHAT'S INCLUDED







- Headlamp

- Li-ion Battery

- Heavy-duty rubber head strap

- 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord

- Instruction Manual

FL 1 STANDARD	SPOT HIGH	FLOOD HIGH	DUAL-LIGHT
	275 LUMENS	250 LUMENS	300 LUMENS
	6h	6h	5h
	120m		
	3660cd		
	2m		
	1m		

**Bayco Products, Inc. XPR-5562GX**  
640 S. Sanden Blvd., Wylie, TX 75098

**cULus LISTED**  
E 467756  
ID 4003544  
INTRINSICALLY SAFE  
SECURITE INTRINSEQUE

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
UL listed for use with Bayco Li-Ion Battery Pack 5562-BATT

CLASS I DIV 1 GRPS A-D T4  
CLASS II & III DIV 1 GRPS E-G T135°C  
CLASS I ZONE 0 AEx ia op is IIC T4 Ga  
© II 1 G Ex ia op is IIC T4 Ga

Ex ia op is IIC T4 Ga  
DEMKO 20 ATEX 2267  
IECEX UL 20.0036  
-20°C ≤ Tamb ≤ +40°C  
3.7V/Cell 5562-BATT  
Um 4.2V

**CE 2575**

WARNING: Do not charge battery in a hazardous location  
WARNING: Do not replace battery when an explosive atmosphere is present

SEE INSTRUCTION MANUAL  
VOIR MANUEL

MFG MM-YY



© 2020 Bayco Products, Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates. XPR-5562-Series-20

